



R e m o t e a i r v a l v e s

Function	Port size	Flow (Max)	Individual mounting	Series
3/2 NO-NC, 2/2 NO-NC	1/2" - 3/4" - 1"	17.4 Cv	Inline	

OPERATIONAL BENEFITS

1. Balanced spool, immune to variations of pressure.
2. Short stroke with high flow.
3. The piston (booster) provides maximum shifting forces.
4. Powerful return thanks to the combination of mechanical and air springs.
5. Bonded spool with minimum friction, shifting in a glass-like finished bore.
6. Wiping effect eliminates sticking.
7. Low leakage rate.



- 1100
- 55
- 56
- 57**
- 58
- 59
- 700
- 900
- 82
- 6300
- 6500
- 6600
- 2700
- 1800
- ISO 1
- ISO 2
- ISO 3

HOW TO ORDER

Port size	Air spring	NC valve	NO valve
1/2" NPTF	Internal	57D-51-RA	57D-81-RA
3/4" NPTF		57D-52-RA	57D-82-RA
1" NPTF		57D-53-RA	57D-83-RA
1/2" NPTF	External	57D-51-RE	57D-81-RE
3/4" NPTF		57D-52-RE	57D-82-RE
1" NPTF		57D-53-RE	57D-83-RE

Air pilot port : 1/8" NPTF.

Note: Designation "RE" required on remote air pilot models with main valve pressures of vacuum to 25 PSI. "RE" provides an external pilot port and should have a pressure range of 25-75 PSI. Since the external pilot supplies the air spring, it must not exceed the remote air pilot signal pressure.

TECHNICAL DATA

Fluid :	Compressed air, vacuum, inert gases
Pressure range :	Vacuum to 150 PSI
Air signal pressure :	25 - 150 PSI ≥ main valve pressure
Lubrication :	Not required, if used select a medium aniline point lubricant (between 180°F to 210°F)
Filtration :	40 μ
Temperature range :	0°F to 120°F (-18°C to 50°C)
Flow (at 6 bar, ΔP=1bar) :	1/2" : (11.0 C _v), 3/4" : (15.3 C _v), 1" : (17.4 C _v)
Leak rate :	100 cm ³ /min

- Spare parts : • Remote air pilot block : R-59003. • Check valve : 70019.
- Options : • BSPP threads.

DIMENSIONS

Dimensions shown are metric (mm)

